

Door Contact DC-7, DC-8 & DCA-8

The Door Contact offers not only reliable monitoring of your doors and windows for their “**OPEN**” & “**CLOSE**” status and to alert the System Control Unit of any irregular activities, but also aesthetic design for today’s modern homes. The **built-in Extension Terminal** allows it to be added to an existing wired sensor, thus makes it doubles as a **Universal Transmitter**.



Features:

- Simple design for easy mounting on door frame
- Tamper protection protects the enclosure from being opened or removed from its mounting surface
- Randomized Supervision signals for trouble-free system integrity checking
- Low Battery detection
- Built-in Auxiliary Input Terminal for Enhanced Flexibility to add Wired Detectors
- Built-in Reed Switch and External Contact can be used simultaneously
- Powerful magnet that gives **30mm Space** between the Door Contact and magnet
- Built-in Extension Terminal for enhanced flexibility to add wired detectors
- LED: Fault & Test Mode Indicator
- Complied with CE requirements

Specifications:

- Power: Alkaline AAA batteries x 2
- Battery life: 3 years or over¹
- Radio frequency available:

DC-7:	433 MHz
DC-8:	868.6375 MHz Narrow FM
DCA-8:	868.35 MHz
- Range:

433 MHz or 868.35 MHz:	over 200 meters in open space
868.6375 MHz:	over 300 meters in open space
- Operating temperature: -20° to 50°C
- Humidity: up to 95% non-condensing
- Dimensions: 135 X 33 X 22 mm

* Note¹: Battery life is calculated at an average of 20 activations per day.

Technoshield Security Systems

Website: <http://www.cyprussecurityspecialists.com>

Email: sales@cyprussecurityspecialists.com