

Door Contact DC-9 & DCA-9

The Door Contact offers not only reliable monitoring of your doors and windows for their “**OPEN**” & “**CLOSE**” status and to alert the System Control Unit of any irregular activities, but also aesthetic design for today’s modern homes.

DC-9 & DCA-9 is **compact & slim in design** and uses Lithium battery, thus has longer battery life. In addition, it is tamper-proof against opening of its enclosure and removal from its mounting surface, and sends regular supervision signals to check system integrity. The **built-in Extension Terminal** allows it to be added to an existing wired sensor, thus makes it doubles as a **Universal Transmitter**.



Features:

- Powered by pre-inserted **Lithium** battery for easy Installation
- Compact & slim design for easy mounting on door frame
- Tamper protection protects the enclosure from being opened or removed from its mounting surface
- Randomized Supervision signals for trouble-free system integrity checking
- Low Battery detection
- Built-in Auxiliary Input Terminal for Enhanced Flexibility to add Wired Detectors
- Built-in Reed Switch and External Contact can be used simultaneously
- Powerful magnet that gives **30mm Space** between the Door Contact and magnet
- Built-in Extension Terminal for enhanced flexibility to add wired detectors
- LED: Fault & Test Mode Indicator
- Complied with CE requirements

Specifications:

- Power: Lithium 1/2 AA batteries x 1 (pre-inserted)
- Battery life: 4 years or over¹
- Radio frequency available:

DC-9-433:	433 MHz
DC-9-866:	868.6375 MHz Narrow FM
DCA-9:	868.35 MHz
- Range: 433 MHz or 868.35 MHz: over 200 meters in open space
868.6375 MHz: over 300 meters in open space
- Operating temperature: -20° to 50°C
- Humidity: up to 95% non-condensing
- Dimensions: 103 X 31 X x 21 mm

* Note¹: Battery life is calculated at an average of 20 activations per day.

Technoshield Security Systems
Website: <http://www.cyprussecurityspecialists.com>
Email: sales@cyprussecurityspecialists.com

