MAGIC CAMERA

MAGIC CAMERA Vivid Color In Low Lux, No IR Needed



. Built-in 1/3" CCD High Resolution Color Camera

FEATURES

. No IR required at night. Clear image under faint start light.


. No overheat problem. Good for energy conservation and conforms to the environmental protection


. Horizontal Resolution 560 TV Lines.

- . IP66 weatherproof housing
- . Hidden-cable Bracket



Material	Aluminum	
Swivel Angle	360°	
Tilt Angle	120°	
Dimension(mm)	208(L)X75(W)X115(H)	
Max. Load	10kg	





▶ SPECIFICATIONS

Model Nur	nber	MAGIC-MS2-02	MAGIC-HS2-02	Outdoor Performance Comparison at Nigl
Scanning	NTSC	525 lines 2:1 interlace		Picture Taken at 6:50PM
System PAL		625 lines 2:1 interlace		
Scanning Frequency PAL	15,734Hz(H) , 60Hz(V)			
	15,625Hz(H) , 50Hz(V)			
Effective Pixels	NTSC	512(H) x 492(V)	768 (H) x 494(V)	Magic of Son Y CCD
	PAL	512(H) x 582(V)	752 (H) x 582(V)	w/ 6mm Len (480TVL)
Electronic	NTSC	1/60-100,000sec.		
Chutter	PAL	1/50-100,000sec		Manager Character
mage Device 1/3" SONY Super HAD CCD		D		
		560 TV lines Enhanced	Normal Sony CCD	
Sensitivity		0.01Lux	0.02Lux	w/ 6mm Ler (420TVL)
Signal to Noise More than 48dB			Magic Camera shows clear color picture w	
Gain Control Auto + 18dB Max		Normal Camera has turned black and whi		
Vhite Balance Auto ATW 2500-9500 °K		Performance Comparison Inside Contro		
Sense-UP times	IP times Max 32 times		Environment of 0.21 LUX	
BLC		Auto		
Gamma Correction		0.45		at a constant of the constant
SYNC System In		Internal		
Lens/Focus point 20mm (Optional 30mm)				
Video Output		1.0 Vp-p, 75 Ohm		w/6mm Len (480TVL)
Protection Class		IP 66		Contract and solar and
Power Requirement (±10%) DC12V				
Power Consum (±10%)	ption	80mA		Normal SONY CCD
Construction		Aluminum with sunshield weatherproof		(420TVL)
Operation Temp. Operating: -20 ~ + 55 °C , Storage: -30 ~ + 80 °C Humidity:0~95%RH		storage: -30 ~ + 80 ℃ ,	Magic Camera maintains an outstanding p mance of clear color picture while Normal Camera has already lost a lot of visibility.	
Dimensions (m	nm)	95(W) x 95(H) x 250(L)		
Weight (N.W)		Approx. 1.9kg (with bracke	et)	
Design and spe	cification	s are subject to change with	out notice.	