

VARI-FOCAL DOME CAMERA




► FEATURES

- . Sony Hi-Res. Star Light Camera
- . Built-in Vari-focal auto iris 3-12mm lens
- . Built-in DNR (Digital Noise Reduction)
- . High quality picture, aesthetic and easy to install
- . Day Night function

► SPECIFICATIONS

| Model Number | | NT-DMS-VF | NT-DHS2-VF |
|-----------------------|------|---------------------------------|--|
| Scanning System | NTSC | 525 lines 2:1 interlace | |
| | PAL | 625 lines 2:1 interlace | |
| Scanning Frequency | NTSC | 15,734Hz(H) , 59.94Hz(V) | |
| | PAL | 15,625Hz(H) , 50Hz(V) | |
| Effective Pixels | NTSC | 510(H) x 492(V) | 768(H) x 494(V) |
| | PAL | 500(H) x 582(V) | 752(H) x 582(V) |
| Electronic Shutter | NTSC | 1/60-100,000sec. | |
| | PAL | 1/50-100,000sec | |
| Image Device | | 1/3" SONY Super HAD CCD | |
| Horizontal Resolution | | 420 TV lines | 560 TV lines Enhanced |
| Sensitivity | | 0.2Lux | 0.001Lux |
| Signal to Noise | | More than 48dB | More than 52dB |
| Gain Control | | AGC | AGC(+18dB) |
| White Balance | | Auto ATW 2500-9500 ° K | |
| Sense-UP times | | - | Max 32 times |
| DNR | | - | Built-in DNR (Digital Noise Reduction) |
| BLC | | Auto | |
| Gamma Correction | | 0.45 | |
| SYNC System | | Internal | |
| Lens/Focus point | | Vari-focal auto iris 3.7mm~12mm | |
| Video Output | | 1.0 Vp-p, 75 Ohm | |
| Protection Class | | - | |



| | | |
|---|--|-------|
| Power Requirement ($\pm 10\%$) | DC12V | |
| Power Consumption ($\pm 10\%$) | 80mA | 110mA |
| Operation Temp. | Operating: $-10 \sim +55$ °C , Storage: $-30 \sim +70$ °C , Humidity:0~95%RH | |
| Dimensions (mm) | 100(R) x90(H) | |
| Weight (N.W) | Approx 300g | |
| Design and specifications are subject to change without notice. | | |