

15M IR CONCEALED CAMERA

L4 Series



► FEATURES

- . Camera lens behind by the special front cover
- . Ceiling mount spot light outlook with camera embedded
- . 1/3" color CCD sensor for clear video output
- . Built-in Mega pixel lens
- . Optical distortion corrective, TV distortion <1%
- . Increase night vision sensitivity of CCD camera

► SPECIFICATIONS

Model Number		CC-MS-L4-I	CC-HS-L4-I
Scanning System	NTSC	525 lines 2:1 interlace	
	PAL	625 lines 2:1 interlace	
Scanning Frequency	NTSC	15,734Hz(H) , 60Hz(V)	
	PAL	15,625Hz(H) , 50Hz(V)	
Effective Pixels	NTSC	512(H) x 492(V)	768 (H) x 492(V)
	PAL	512(H) x 582(V)	752 (H) x 582(V)
Electronic Shutter	NTSC	1/60-100,000sec.	
	PAL	1/50-100,000sec	
Image Device		1/3" SONY Super HAD CCD	
Horizontal Resolution		420 TV lines	540 TV lines
Sensitivity		0.2Lux, 0 Lux at IR on	0.5Lux, 0 Lux at IR on
Signal to Noise		More than 48dB	
Gain Control		Auto	
White Balance		Auto ATW 2500-9500 ° K	
Sense-UP times		-	
DNR		-	
BLC		Auto	
Gamma Correction		0.45	
SYNC System		Internal	
Lens		Mega pixel Lens 4.0mm	
Video Output		1.0 Vp-p, 75 Ohm	
IR LED		12 units 940nm infrared LED	
IR Distance		15 meters (Subject to IR reflection conditions)	
IR Status		IR on: Under 10 Lux, by CDS auto control	
LED life		More than 10,000 Hours	

Protection Class	-
Power Requirement ($\pm 10\%$)	DC12V, 500mA
Power Consumption ($\pm 10\%$)	IR on: 180mA, IR off: 80mA
Operation Temp.	Operating: -10 ~ + 55 °C , Storage: -30 ~ + 70 °C , Humidity:0~95%RH
Dimensions (mm)	128(R) x 84(H)
Weight (N.W)	0.24kg
Design and specifications are subject to change without notice.	