

PBS320AF



Synchronous Focus Mini Speed Dome

- 1) 1/3" SONY CCD, 420 /540 /600TVL
- 2) 5-15mm auto focus lens
- 3) With RS485 Remote Control
- 4) Memory function at accidental power -off
- 5) Support Pelco P / D Protocol

Application:

Mega pixel motorized zoom lens, remote control, main used in hotel, restaurant, school, office, bank, hospital, etc.

Product Features:

- 1) 1/3" SONY CCD+SONY CCD, 420 /540 /600TVL
- 2) 4-9mm / 5-15mm / 8-20mm motorized zoom lens
- 3) Audio function is optional
- 4) Min. Illumination: 0.01lux
- 5) Super Wide Voltage board: 8-18V
- 6) In-built RS485 signal out line controller
- 7) Color and W/B is Auto-change
- 8) Memory function

Model	PBS-320AF	PBS-320AF
Image Sensor	1/3"SONY CCD	1/3"SONY CCD
Digital Singnal Processor	SONY DSP	SONY DSP
Signal System	PAL / NTSC	
Scanning System	2:1 Interlace	
Scanning Frequency(H)	NTSC:15.734KHZ , PAL:15.625KHZ	
Sync. System	Internal	
Horizontal System	540TVL	420TVL
Effective Pixels (HxV)	PAL:752x582	PAL:500x582
	NTSC:768x494	NTSC:510x492
Shuttle Speed	PAL=1/50 ~1/100,000 sec ; NTSC=1/60 ~1/100,000 sec	
Mini Illumination	0.01 Lux	
S/N Ratio	> 48dB (Auto Gain Off)	
Gamma	0.45	
Lens	4-9mm / 5-15mm / 8-20mm motorized zoom lens	
Focus Mode	Auto	
White Balance	AUTO	
BLC	Open	
Video Output	1.0V P-P,75Ω	
AGC	Auto	
Input/Output Connector	Power: 2 Pin Terminal/ RS-485: 2 Pin Circle Connector/ Video Output: 1 BNC Connector	
Operating Voltage	Super Wide Voltage (8V~18V)	
CCD board Consumption	120mA	80mA
Operating Temperature	-10 ~ 40°C (relative humidity:the most 95%)	