

## Smoke Detector SD-7, SD-8 & SDA-8

Smoke Detector is a low profile and the smallest in size that utilizes the latest Optical Chamber technology to free it from potentially harmful radioactive materials. It is micro-process controlled and offers 100% Reliability, Safety and Quality you can ever get.



### Features:

- Excellent stability with high sensitivity
- Detection method: Reflective photoelectric sensor
- Digital Signal Processing
- Randomized supervision signals for trouble-free system integrity checking
- Low Battery detection
- Diagnostic function: a Test button for self-test including optical sensor diagnosis
- Alarm silence function: 10 minutes per activation
- Built-in siren for audio alert
- Alarm Volume: 95 dB @ 1 meter
- Certification: Sensitivity **EN54-7** certified
- **Specifications:**
- Power: Alkaline AAA x 4
- Battery life: 3 years or over<sup>1</sup>
- Radio frequency available:
 

SD-7:	433 MHz
SD-8:	868.6375 MHz FM
SDA-8:	868.35 MHz
- Range:
 

433 MHz or 868.35 MHz:	over 200 meters in open space
868.6375 MHz:	over 300 meters in open space
- Operating temperature: -20° to 50°C
- Humidity: up to 95% non-condensing
- Dimensions: Ø105 X 42 mm

\* Note<sup>1</sup>: Battery life is calculated at an average of 1 activation per day.

Technoshield Security Systems  
 Website: <http://www.cyprussecurityspecialists.com>  
 Email: [sales@cyprussecurityspecialists.com](mailto:sales@cyprussecurityspecialists.com)

