

## RF ID Tag Reader TG-7, TG-8 & TGA-8

### – Arm and Disarm Panel by Tags

Tag Reader TG-7/8 offers a wireless, versatile, and simple solution to easily access your security system. It allows you to securely “Arm” and “Disarm” the system by recognizing the user’s RFID. You can simply wave a RFID Tag in front of the Tag Reader without the hassle of using or memorizing any PIN code – making home security simple and convenient!



#### Features:

- Capability to store up to 6 tags
- Battery operated
- Arm/disarm the alarm system
- Compatible with all existing Climax alarm panel systems
- Power conservation – consumes power in operation only
- Low battery detection
- Tamper protection – protects the enclosure from being opened or removed from its mounting surface
- Complied with CE & FCC requirements

#### Specifications:

- Power: Alkaline AAA batteries x 3
- Battery life: 4 years (at 2 activations per day)
- RF ID sensing distance: 6 cm
- RF ID frequency: 13.56 MHz
- Protocol: ISO 15693
- Radio frequency available:
 

TG-7:	433 MHz
TG-8:	868.6375 MHz Narrow FM
TGA-8:	868.35 MHz AM
- Range:
 

433 MHz or 868.35 MHz:	over 200 meters in open space
868.6375 MHz:	over 300 meters in open space
- Operating temperature: -10° to 50°C
- Humidity: up to 85% non-condensing
- Dimensions: 129.42 X 94 X 26.68 mm



Technoshield Security Systems

Website: <http://www.cyprussecurityspecialists.com>

Email: [sales@cyprussecurityspecialists.com](mailto:sales@cyprussecurityspecialists.com)